



Dutch Masters

Product Specifications

Brick Type	Typical Work Size mm	Frost Resistance	Water Absorption %	Compressive Strength N/mm ²	Soluble Salts %
FB GD	213 x 95 x 65	C	17	25	0.02
FB Rustiek	213 x 95 x 65	C	19	25	0.02
FB Havana Coal Flecked	210 x 95 x 65	C	16	35	0.01
FB Carmine Red	210 x 95 x 65	C	19	27	0.01
FB Carmine Multi	210 x 95 x 65	C	18	35	0.01
FB L Standard	210 x 95 x 65	C	17	25	0.02
FB L Coal Flecked	210 x 95 x 65	C	19	25	0.02
JK Old Maas	208 x 100 x 65	C	20	23	0.02
JK Old Maas Coal Flecked	208 x 100 x 65	C	20	23	0.02

Manufactured to comply with Dutch Standard NEN 2489

Terca Schouderden

Product Specification

Brick Type	Typical Work Size mm	Durability Designation	Water Absorption %	Compressive Strength N/mm ²	Soluble Salts %
Old York Russet	205 x 100 x 65	FL	< 20	> 10	Low
Walmgate Multi	215 x 102 x 65	FL	< 20	> 10	Low
Ousgate Red	208 x 102 x 65	FL	< 20	> 10	Low
York Russet Antique	208 x 98 x 63	FL	< 20	> 10	Low

Manufactured to comply with DIN 105

E.Power, Technical Manager
8th June 2004